

## Certificate of Conformity of the Factory Production Control 2195-CPR-1415703

In compliance with Regulation 305/2011/EU of the European Parliament and of the Council of 9 March 2011 (the Construction Products Regulation or CPR), this certificate applies to the construction product

### Aluminium and Aluminium Alloys-Structural Products for Construction Works

(tested for performance for the characteristics described in Annex 1 which is an inseparable part of this certificate)

produced by the manufacturer

**ASSAN ALÜMİNYUM SAN. VE TİC. A.Ş.**

Yayla Mahallesi D-100 Karayolu Rüya Sok. No:2, 34940 Tuzla / İstanbul – Turkey

and produced in the manufacturing plant

**ASSAN ALÜMİNYUM SAN. VE TİC. A.Ş.**

Plant 1: Yayla Mahallesi D-100 Karayolu Rüya Sok. No: 2, 34940 Tuzla / İstanbul – Turkey  
Plant 2: Dilovası Organize San. Böl.1. Kısım Dicle Sok. No: 40, 41455 Kocaeli – Turkey

*This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in Annex ZA of the standard(s)*

**EN 15088:2005**

*under system 2+ are applied and that the factory production control is assessed to be in conformity with the applicable requirements. This certificate was first issued on 06.06.2014, renewed on 06.06.2020 and will remain valid as long as neither the harmonised standard, the construction product, the assessment and verification of constancy of performance methods nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the notified factory production control certification body. The certificate is supported through annual surveillance audit and is reissued after each surveillance audit, this certificate should be reissued not later than 06.06.2021.*



Rukiye BALKAN  
Deputy General Manager

## Certificate of Conformity of the Factory Production Control 2195-CPR-1415703

### Annex 1

#### Intended uses;

To be used in metal structures or in composite metal structures in buildings and civil engineering

#### Controlled Performance Characteristics;

- Chemical Composition,
- Dimension and Shape Tolerances,
- Yield Strength,
- Elongation,
- Tensile Strength,
- Durability.

Products	General Conditions	Specific Conditions			Sizes	Alloys
		Chemical spec.	Mechanical spec.	Tolerance		
<b>Cold rolled Aluminum sheets, strips, plates</b>	EN 485-1	EN 573-3	EN 485-2	EN 485-4	Wall thickness; 0,20 mm - 6,00 mm	EN AW 1050 EN AW 3003 EN AW 3005 EN AW 3105
<b>Wrinkle Polyester ve Polyester Top coat painted Aluminum sheets, strips, plates</b>	EN 485-1 EN 1396	EN 573-3 EN 1396	EN 485-2 EN 1396	EN 485-4 EN 1396	Wall thickness; 0,30 mm - 3,00 mm*	EN AW 5005 EN AW 5754

(\*) Primer thickness is max 5 µm, top coat paint thickness is max 22 µm.



Rukiye BALKAN  
Deputy General Manager